



**MELF FUSIBLE RESISTORS**  
**COATED TYPE**
**MELF熔断电阻**  
**晶圆熔断电阻**
**QUICK REFERENCE DATA**
**技术参数**

Type	RRM73P	RRM74M	RRM74P	RRM16M	RRM17M	型号	
Metric type	DIN: 0204		DIN: 0207		DIN: 0411	德国工业标准型号	
RCD type	FC1206	FC1210	FC2010	FC2012		CECC 型号	
Resistance range	1 Ω to 10 k Ω					Vishay 公司型号	
Resistance tolerance	F(±1%); J(±5%)					阻值范围	
Temperature coefficient	C3(±25ppm/°C); C2(±50ppm/°C); C1(±100ppm/°C)					精度	
Climatic category (LCT/UCT/days)	55/125/56					温度系数	
Rated dissipation, $P_{70}$	0.25W	0.50W		1.0W	2.0W	70°C 以下额定功率	
Operating voltage $U_{max}$	250V	250V	300V	350V	400V	$U_{max}$ 最大工作电压	
Temperature range	-55°C to 125°C					工作温度范围	
Insulation voltage	300V	500V	600V	700V	800V	绝缘耐压	
Insulation resistance	1G					绝缘阻抗	
Dimension	±0.2mm	L=3.5; L1=1.8; D=1.4	L=5.7; L1=2.8; D=2.1		L=6.0; L1=3.1; D=2.1	L=8.7; L1=4.8; D=3.1	外型尺寸
	±0.1mm	$K_{min}=0.8; D1=D+0/D-0.15$	$K_{min}=1.0; D1=D+0 / D-0.25$		$K_{min}=1.0; D1=D+0/D-0.25$	$K_{min}=1.5; D1=D+0/D-0.35$	
Soldering pad (recomanded)	S=1.6; W=2.5; H=2.5	S=2.6; W=2.5; H=2.5		S=2.8; W=2.8; H=2.8	S=5.6; W=3.2; H=3.8	建议焊盘尺寸	
Outlines						外观	